

Type of Appliance

- Temperature controlled, continuous flow, gas hot water system
- Certified for installation in manufactured (mobile) homes
- Forced combustion / Direct vent
- Energy Star qualified

Rinnai Model Number

REU-VC2528FFUD-US

Minimum/Maximum Gas Rate (Input)

10,300 - 180,000 BTU/h

Electrical

Appliance: AC 120 Volts - 60 Hz
 Controller: DC 12 Volts

Electrical Consumption

Normal: 76 w Standby: 2 w Anti-frost protection: 120 w

Ignition System

Direct electronic ignition

Hot Water Capacity

Minimum flow rate: 0.26 GPM
 Minimum activation flow rate: 0.4 GPM
 Maximum flow rate: 7.5 GPM

Temperature

98° - 120° F (factory default) Maximum temperature is selectable at 120° F or at 140° F; 98° - 160° F available with the MCC-91-2 controller for commercial and hydronic applications

Temperature (without remote)

120° F (factory default) or 140° F

Installation

Indoor only

Energy Factor

Natural Gas: 0.82 Propane: 0.82

Service Connections

Gas supply: 3/4 inch MNPT Cold water inlet: 3/4 inch MNPT
 Hot water outlet: 3/4 inch MNPT

Isolation & Pressure Relief Valves Included

Heavy duty forged brass Webstone Isolator valves EXP E2, certified to NSF/ANSI 61-8 for potable water

Water Flow Control


Water flow sensor, electronic water control device and fixed by-pass

Minimum/Maximum Water Supply Pressure

20 - 150 PSI (recommended 30-80 PSI for maximum performance)

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.

FLOW TABLE



Water Temperature Control

Controller

Simulation feed forward and feedback

MC-91-2US (part of the front panel)

Deluxe controller: MC-100V-1US (optional)

Bathroom controller: BC-100V-1US (optional)

MCC-91-2US (optional; for hydronic and commercial applications)

Controller Cable

Non-polarized two-core cable, minimum 22 AWG

Safety Devices

- Flame failure - Flame Rod
- Boiling protection
- Combustion fan rpm check
- Over current - glass fuse
- Remaining flame (OHS)
- Thermal fuse
- Automatic frost protection

Clearances from Combustibles (suitable for closet, attic, and crawl space installations)

- Top of heater - 6 inches
- Front of heater - 6 inches
- Sides of heater - 2 inches
- Back of heater - 0 inches
- Ground / bottom - 12 inches
- From vent pipe - 0 inches

Clearances from Non-combustibles

- Top of heater - 2 inches
- Front of heater - 6 inches
- Sides of heater - 1/2 inch
- Back of heater - 0 inches
- Ground / bottom - 12 inches
- From vent pipe - 0 inches

Min. / Max. Gas Supply Pressure (sea level)

Natural Gas: min 5" W.C. max 10.5" W.C.
Propane Gas: min 8" W.C. max 13.5" W.C.

Manifold Gas Pressure (inches W.C.)

Natural Gas: high fire 2.5" W.C. low fire 0.61" W.C.
Propane Gas: high fire 3.9" W.C. low fire 0.87" W.C.

NOx

Complies with South Coast Air Quality Management District 14 ng/J or 20 ppm NOx emission levels

Warranty

Heat exchanger: 12 years* for residential, 10 years for residential and space heating, and 5 years* for commercial; All other parts: 5 years*; Labor: 1 year;
(* 3 years if used as a circulating water heater within a circulation loop, when the water heater is in series with a circulation system and all circulating water flows through the water heater, and where an on-demand recirculation system is not incorporated.)

Refer to the manual for complete warranty information.

